



## 技术特点:

- 常规宽度: 1600mm、2200mm
- “三信螺杆”, 优异的塑化质量。耐磨系数高
- 纵向拉伸系统具有高精度速度控制、压力控制、温度控制, 确保透湿度均匀
- 自动穿膜系统
- 集中润滑系统
- 配置深压纹装置
- 快速更换花辊、胶辊设计
- 配置远程诊断功能, 能够第一时间满足客户的要求

## Main Technical Data/Features:

- Width: 1,600mm, 2,200mm.
- We design the SANXIN SCREW to match with resin. High Abrasion Resistance.
- MDO with high accurately speed control, nip pressure control, temperature control, and ensure good WVTR (water vapor transmission rate).
- Automatically Guide Film system.
- Integrate Lubricate system.
- With Deep emboss system.
- Emboss roller dismantle quickly design.
- With Remote Diagnose System.



## 南通三信塑胶装备科技股份有限公司

公司地址: 江苏省启东市台角工业区

网址: [www.ntsaxin.com](http://www.ntsaxin.com)

[www.ntsaxin.cn](http://www.ntsaxin.cn)

总机: 0513-83214154

传真: 0513-83214152

邮箱: [ntsx@ntsaxin.com](mailto:ntsx@ntsaxin.com)

NANTONG SANXIN PLASTICS EQUIPMENT TECHNOLOGY CO.,LTD

Address: Taijiao Industrial Zone, Qidong City, Jiangsu Province, China

Website: [www.ntsaxin.com](http://www.ntsaxin.com)

[www.ntsaxin.cn](http://www.ntsaxin.cn)

Tel: 0086-513-83214154

Fax: 0086-513-83214152

Email: [ntsx@ntsaxin.com](mailto:ntsx@ntsaxin.com)



## PE 透气膜生产线

### PE BREATHABLE FILM LINE

#### 制品应用：

PE透气膜主要用于生理卫生行业，如婴儿尿裤、妇女卫生巾、护垫中，同时还用于一次性手术衣、透气性服装面料、新鲜水果蔬菜保鲜包装、医药包装、建筑木材包覆等要求防水与透气功能兼备的场合。

#### Application of Film:

PE Breathable Film apply to Sanitary Industry, like Baby Diaper, Feminine Napkin and the Shield. Also used in the disposal medicine clothes, breathable garment cloths, package for fresh vegetable, construction wooden packing and other situations both water-resistant and air breathable.

